

VGBA-2017 PRODUCT SPECIFICATIONS

Suction Outlet Fitting Assembly (SOFA)

VGBA-2017 Flow Ratings, Sump Dimensions, Sump Flow Path Zone, and Head Loss Curves




DIRECTIONS: Please follow the SOFA specific flow rates, sump specifications, and flow path zone information below. The installation must conform to these minimum/maximum requirements including the SOFA dimension defined in Figure 1. The flow path zone is defined by dimensions A through E. The installed sump may be manufactured or field-built and it may be larger/deeper than Figure 1. Please write the Cover Model Number, orientation, and SOFA Model Flow Rating on the VGBA DRAIN COVER IDENTIFICATION INFORMATION label that comes with each AquaStar Pool Products, Inc. drain cover.

Cover Model Number: 1216xxx







FOR MOST CURRENT INFORMATION SCAN THE QR CODE OR VISIT


WWW.AQUASTARPOOLPRODUCTS.COM/FLOWCODE PRINTED DOCUMENTS MAY NOT HAVE THE MOST CURRENT FLOW RATINGS OR INSTALLATION OPTIONS.




Minimum Ledge Depth Maximum Ledge Width Minimum Pipe Offset Minimum Length Before Reduction

SOFA Model No.		Pipe Size (Nominal)	Pipe Depth (Minimum)	Orientation (Wall / Floor)	Flow Rating (GPM)	Head Loss Curve
1216-12f_A-1.5b_B3_C0.3_D0.7_E3.5_F16		1.5" (b)	3"	Floor (f)	126	Α
1216-8f_A-2s_B1.6_C0.4_D0.5_E2.4_F16		2" (s)	1.6"	Floor (f)	150	В
1216-9f_A-2b_B3_C1.6_D0.5_E2.8_F16		2" (b)	3"	Floor (f)	200	С
1216-8f_A-2.5b_B3_C0.4_D0.4_E2.3_F16		2.5" (b)	3"	Floor (f)	250	D
1216-9f_A-3b_B3_C1.6_D0.5_E2.5_F16		3" (b)	3"	Floor (f)	320	E
1216-9f_A-4b_B9.8_C1.6_D0.5_E1.8_F16		4" (b)	9.8"	Floor (f)	584	F
1216-12f_A-4s_B6_C0.3_D0.7_E3_F16	[Sump P/N 12-3SB]	4" (s)	6"	Floor (f)	500	G
1216-12f_A-4s,2.5b_B6_C0.3_D0.7_E3_F16	[Sump P/N 12-3SB]	4"(s), 2.5" (b)	6"	Floor (f)	626	Н
1216-12f_A-6b_B10.5_C0.3_D0.7_E3_F16	[Sump P/N 12-6SB]	6" (b)	10.5"	Floor (f)	720	I
1216-12w_A-1.5b_B3_C0.3_D0.7_E3.5_F16		1.5" (b)	3"	Wall (w)	126	J
1216-12w_A-2b_B3_C0.3_D0.7_E3.5_F16		2" (b)	3"	Wall (w)	150	K
1216-12w_A-2.5b_B3_C0.3_D0.7_E4.7_F16		2.5" (b)	3"	Wall (w)	250	L
1216-12w_A-3b_B3_C0.3_D0.7_E4.2_F16		3" (b)	3"	Wall (w)	320	М
1216-9w_A-4b_B9.8_C1.6_D0.5_E1.8_F16		4" (b)	9.8"	Wall (w)	400	N
1216-12w_A-6b_B10.5_C0.3_D0.7_E3_F16	[Sump P/N 12-6SB]	6" (b)	10.5"	Wall (w)	540	0

Note 1: "SOFA Model No" nomenclature; bottom pipe = (b), sde pipe = (s). See Fig 1 for capital letters A through E Note 2: Head loss inHg is measured 16 to 24 inches from the finish surface of the pool. Reference Fig 1 dimension F.





© 2021 AquaStar Pool Products. Inc. All rights reserved.

11032021