24" SQUARE FRAME WITH FOUR 12" SQUARE FLAT GRATE ANTI-ENTRAPMENT SUCTION OUTLET COVERS





VGB CERTIFIED

SPECIFICATIONS

Floor Flow Rating 1531 GPM at 1.4 fps Wall Flow Rating 1531 GPM at 1.4 fps **Sump Depth** 12" minimum

Open Area 352 in²

FEATURES

All components meet or exceed ANSI/APSP 16-2011 and NSF/ANSI 50-2009a national standards and ASTM G154 UV testing exposure

Installs flat – level with finish

Manufactured from superior UV-resistant engineered polymers

#316 stainless steel screws

Online product support including downloadable CAD files, General Certificate of Conformity, third-party certificate, installation instructions and more

Trademarked VGB compliance button easily identifies VGB 2008 compliant cover from on deck and underwater


Replace drain cover every five years from the date of installation

1 per case

No Frame - DMS24NF

Unblockable! No second suction outlet or backup SVRS required





Part # 24xxx

 $\label{eq:Fits: AquaStar standard 24" models and American (Pentair) with 34'' deep existing window grid frame and 4x4 screw hole pattern.$


STANDARD COLORS


- 24101 White
- 24102 Black
- 24103 Light Gray
- 24104 Blue
- 24105 Dark Gray
- 24108 Tan

Also available with four grates for ¾" deep retrofits p/n 24NFxxx

Replaces p/n WAV24xxx, P24xxx

VGB 2008 Compliant





- 1. 24" Square Mud Frame
- 2. 12" Flat Square Suction Outlet Cover, Qty 4
- 3. 10 x 3/4" Flat Head Phillips Screw, 316 SS, Qty 16