

- GENERAL NOTES:


  1. MEDIA NOT INCLUDED WITH FILTER
  2. CONCRETE SLAB TO BE DESIGNED BY OTHERS
  3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS
  AND RESINS
  4. FILTERS HAVE UV STABILIZED CLEAR COAT
  5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF
  SCHEDULE 80 PVC.
- SCHEDULE AND BE LOCATED ON EITHER SIDE OF FILTER. PLEASE SPECIFY AT TIME OF ORDER. 7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.


FILTER DATA					
TOTAL SURFACE AREA:	46 SQ. FT.				
MAX WORKING PRESSURE:	50 PSI.				
MAX FLOW RATE:	20 GPM / SQ. FT.				
MEDIA REQUIREMENTS					
SAND:	5,400 LBS				
GRAVEL:	3,100 LBS				
WEIGHTS					
FILTER SHIPPING WEIGHT	1,365 LBS				
FILTER OPERATING WEIGHT:	17,480 LBS				



HORIZONTAL SAND FILTER (20902) 63"x106" WITH 8" 4 VALVE MANIFOLD

DRAWN BY:	MM	DWG. NO:	0902-2	REV:
SCALE: 3/8" = 1'	DATE:	10/30/02	CHECKED:	





- GENERAL NOTES:


  1. MEDIA NOT INCLUDED WITH FILTER
  2. CONCRETE SLAB TO BE DESIGNED BY OTHERS
  3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND RESINS
  4. FILTERS HAVE UV STABILIZED CLEAR COAT
  5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 80 PVC.
  6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER. PLEASE SPECIFY AT TIME OF ORDER.
  7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.


FILTER DATA					
TOTAL SURFACE AREA:	46 SQ. FT.				
MAX WORKING PRESSURE:	50 PSI.				
MAX FLOW RATE:	20 GPM / SQ. FT.				
MEDIA REQUIREMENTS					
SAND:	5,400 LBS				
GRAVEL:	3,100 LBS				
WEIGHTS					
FILTER SHIPPING WEIGHT	1,365 LBS				
FILTER OPERATING WEIGHT:	17,530 LBS				




# HORIZONTAL SAND FILTER (20902) 63"x106" WITH 8" 5 VALVE MANIFOLD

DRAWN BY:	V	IM	DWG. NO:	2	0902-3	REV:
SCALE: 3/8" = 1'		DATE:	10/30/02		CHECKED:	








- GENERAL NUTES: 1. MEDIA NOT INCLUDED WITH FILTER
- 2. CONCRETE SLAB TO BE DESIGNED BY OTHERS
- 3. FILTER MADE FROM HIGH STRENGTH FISERGLASS AND RESINS
- 4. FILTERS HAVE UV STABILIZED CLEAR COAT
- 5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 30 PVC
- 6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER, PLEASE SPECIFY AT TIME OF ORDER.
- 7. SAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.


FILTER DATA					
TOTAL SURFACE AREA:	46 SQ. FT.				
MAX WORKING PRESSURE:	50 PSI.				
MAX FLOW RATE:	20 GPM / SQ. FT.				
MEDIA REQUIREMENTS					
SAND:	5,400 LBS				
GRAVEL:	3,100 LBS				
WEIGHTS					
FILTER SHIPPING WEIGHT	1,365 LBS				
FILTER OPERATING WEIGHT:	17,150 LBS				




# HORIZONTAL SAND FILTER (20902) 63"x106" WITH 8" CONNECTIONS

DRAWN BY:	MM	DWG. NO:	0902	REV:
SCALE: 3/8" = 1'	DATE:	10/21/02	CHECKED:	







- GENERAL NOTEA:

  1. MEDIA NOT INCLUDED WITH FILTER


  2. CONCRETE SLAB TO BE DESIGNED BY CTHERS
- 3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND REALNS
- 4. FILTERS HAVE UV STABILIZED CLEAR COAT
- 6. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 60 PVC.
- 6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER. FLEASE SPECIFY AT TIME OF ORDER.
- 7. BAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.


FILTER DATA					
TOTAL SURFACE AREA:	92 SQ. FT.				
MAX WORKING PRESSURE:	50 PSI.				
MAX FLOW RATE:	20 GPM / SQ. FT.				
MEDIA REQUIREMENTS					
SAND:	5,400 LBS EA				
GRAVEL:	3,100 LBS EA				
WEIGHTS					
FILTER SHIPPING WEIGHT	1,365 LBS EA				
FILTER OPERATING WEIGHT:	34,900 LBS				




**DUAL HORIZONTAL FILTER (20902)** 63"x106" W/ 8" 4 VALVE MANIFOLD

DRAWN BY: MM		DWG. NO: 20902-5		REV:
SCALE: 1/4" = 1'	DATE:	10/30/02	CHECKED:	







- GENERAL NOTEA:

  1. MEDIA NOT INCLUDED WITH FILTER

  2. CONCRETE SLAB TO BE DESIGNED BY CTHERS
- 3. FILTER MADE FROM HIGH STRENGTH FIBERGLASS AND REALNS
- 4. FILTERS HAVE UV STABILIZED CLEAR COAT
- 5. ALL INTERNAL COMPONENTS ARE CONSTRUCTED OF SCHEDULE 80 PVC.
- 6. MANHOLE CAN BE LOCATED ON EITHER SIDE OF FILTER. FLEASE SPECIFY AT TIME OF ORDER.
- 7. BAND DRAIN AND WATER DRAIN ARE PLACED ON THE SAME SIDE AS THE MANHOLE.

FILTER DATA				
TOTAL SURFACE AREA:	92 SQ. FT.			
MAX WORKING PRESSURE:	50 PSI.			
MAX FLOW RATE:	20 GPM / SQ. FT.			
MEDIA REQUIREMENTS				
SAND:	5,400 LBS EA			
GRAVEL:	3,100 LBS EA			
WEIGHTS				
FILTER SHIPPING WEIGHT	1,365 LBS EA			
FILTER OPERATING WEIGHT:	34,900 LBS			



**DUAL HORIZONTAL FILTER (20902)** 63"x106" W/ 8" 5 VALVE MANIFOLD

DRAWN BY: MM		DWG. NO: 20902-6		REV:
SCALE: 1/4" = 1'	DATE:	10/30/02	CHECKED:	