


Harmsco® Betterfilters® for Commercial and Public Pools



Harmsco Betterfilters provide sparkling clean water and save energy and space.

Betterfilters are constructed of low carbon T-304 stainless steel, Electro-chemically polished to deliver a ten year pro-rated warranty.

Harmsco filters install quickly and easily, require no costly waste disposal systems, and come ready for use with Harmsco's reusable SuperTuf/6™ Polyester-Plus Cartridges for maximum operating performance and a long service life.



Cartridge lifters remove easily for cleaning or replacement.



Model No.	Max. NSF Flow Rate* Public Pools	Max. NSF Pool Size Public Pools	Number Of Cartridges	Filter Area	Height	Height Clearance	Service Floor Space	Pipe In and Out	Approx. Shipping Weight
BF168	63 GPM	22,680 Gals.	28	168 FT ²	30"	48"	18" x 18"	2" NPT	82 lbs.
BF252	94.5 GPM	34,020 Gals.	42	252 FT ²	40"	68"	18" x 18"	2" NPT	101 lbs.
BF336	126 GPM	45,360 Gals.	56	336 FT ²	52"	87"	18" x 18"	3" NPT	125 lbs.
BF450	168.75 GPM	60,750 Gals.	75	450 FT ²	42"	73"	20" x 20"	3" NPT	169 lbs.
BF600	225 GPM	81,000 Gals.	100	600 FT ²	52"	90"	20" x 20"	3" NPT	195 lbs.
BF900FL	337.5 GPM	121,500 Gals.	150	900 FT ²	48"	76"	28" x 28"	4" Flange	291 lbs.
BF1200FL	450 GPM	162,000 Gals.	200	1200 FT ²	58"	93"	28" x 28"	4" Flange	328 lbs.

10 year pro-rated limited warranty on all Harmsco filters prepared for fresh-water service. 1 year warranty on all Harmsco filters prepared for salt-water service.

All Harmsco Betterfilters are NSF Certified for commercial pool applications. Harmsco and Betterfilters and SuperTuf are registered trademarks of Harmsco, Inc.

Note: Salt water units have identical capabilities and dimensions. SW is added to model designation to indicate units prepared for salt (Example: Betterfilter 450SW).

Initial pressure drop across any commercial unit at NSF tested and certified flow rates never exceeds 3 psi. (0.2 BAR).

Heavy swim loads require additional filter area.

MADE IN U.S.A.

