



GLASS BEAD PLASTER FOR UNDERWATER OR ABOVE WATER FAST SET REPAIRS

E-Z INSTRUCTIONS:

UNDER WATER REPAIRS:

1. Remove loose cement and chip area at least 3/8" deep. Make sure the edges are chipped straight down (not beveled or slanted). Clean the surface.
2. Add water sparingly to **E-Z PATCH® 11 F.S.** DRY CEMENT MIX and mix it into a very thick consistency enough to be used within 5 min. Use warm water for even faster set and cold water to slow set.
3. Wait a couple of minutes (until the materials start to harden), place a little more than needed in your hand or plastic bag. Install **E-Z PATCH® 11 F.S.** firmly on the area.
4. Slowly flatten smooth and flush with a trowel = flush with the existing plaster & clean edges with a sponge. Expose the glass beads lightly with a sponge. Slowly back away from repair. **Allow repair to set hard before swimming.**

ABOVE WATER REPAIRS:

1. Follow steps 1. & 2. above, but add a little more water.
- 2a. **CRACK REPAIRS:** Cut crack 3/8" wide & 3/8" deep, clean surface, rub **E-Z PATCH® 11 F.S.** deep into crack and remove excess and expose the Glass Beads with a moist sponge.
- 2b. **CHIPS OR LARGER AREAS:** Firmly trowel **E-Z PATCH® 11 F.S.** filling the area. Trowel flat and smooth. Remove excess from edges with a moist sponge. Fine spray with a water hose, bug sprayer or use a wet sponge to expose the Glass Beads. If there is any residue "haze" the next day, it can be removed by wetting the surface with water & pouring a mixture of 1/3 muriatic acid to 2/3 water on the patched area. Wait 1 minute and rinse using a water hose.

Allow repair to set hard before filling pool.

To make a Custom Color with any of our cement type repair supplies, use any cement dye.

View our instructional repair video showing how to do this repair at www.e-zpatch.com

E-Z ANSWERS to some Frequently Asked Questions

- **Fast Set formulas do not require Liquid Bonder**
- **Product will cure faster in hotter weather, slower in cooler weather**
- **Product is best stored between 30 degrees F and 110 degrees F**

WARNING: CONTAINS CEMENT, AN ALKALINE SUBSTANCE IRRITATING TO EYES AND SKIN. SHOULD PRODUCT CONTACT EYES, FLUSH THEM IMMEDIATELY AND REPEATEDLY WITH WATER AND CALL A PHYSICIAN. DO NOT TAKE INTERNALLY. IN CASE OF SKIN CONTACT, RINSE IMMEDIATELY WITH WATER. USE OF RUBBER GLOVES IS RECOMMENDED.

KEEP OUT OF THE REACH OF CHILDREN