SAFETY DATA SHEET E-Z PATCH® 10

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: E-Z PATCH® #10 (Pool Quartz Dry Mix)	Product Use: Pool Repair Material
Manufacturer's Name: E-Z Products	Emergency Telephone: 888-439-7282 or 480-488-8207
Address: 32449 N. 66th St., Cave Creek, AZ 85331	Telephone Number: 480-488-8207
Date Prepared: May 28, 2015	Date Updated: May 28, 2015

SECTION 2: HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION

Skin Irritation 2 Serious Eye Damage 1 Skin Sensitization 1 Carcinogenicity 1A Specific Target Organ Toxicity – Single Exposure 3 Specific Target Organ Toxicity – Repeated Exposure 1

LABEL ELEMENTS



Signal Word: Caution

Hazard Statement: Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May be harmful if swallowed. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure.

Prevention: Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, and face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. Do not eat, drink or smoke when using this product.

Response: <u>If on skin</u>: Wash with plenty of water. Take off contaminated clothing and wash clothing before reuse. <u>If skin irritation or rash occur</u>s: get medical advice and/or attention. <u>If in eyes</u>: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easily removed and continue rinsing. Immediately call a poison center or doctor. <u>If inhaled</u>: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. <u>If exposed or concerned</u>: Get medical advice and attention.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents and container in accordance with all local, regional, national and international regulations.

ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

40.0 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL OR INGREDIENT	CAS #	WT. %	
Portland Cement	65997-15-1	40-60	
Crystalline Silica Quartz	14808-60-7	40-60	
Limestone	474-34-1	0-15	
Iron Oxide	1309-37-1	0-15	
Calcium Carbonate	1317-65-3	0-5	
Magnesium Oxide 1309-48-4 0.1-2.5			
Inorganic Pigments	various	0-10	
Exact composition percentage/concentration has been withheld as a trade secret in accordance with paragraph (i) of \$1910,1200			

Exact composition percentage/concentration has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: FIRST-AID MEASURES

DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Give 2 cupfuls of water if victim is conscience and alert. Get medical advice/attention.

IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.

Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation. May cause burns in the presence of moisture.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

SECTION 5 - FIRE-FIGHTING MEASURES

FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA criteria.

EXTINGUISHING MEDIA

Suitable Extinguishing Media: Treat for surrounding material. Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Notavailable.

SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data: Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN - UP

Methods for Containment: Contain spill with inert material (sand, vermiculite, etc.) and place in a suitable container. Do not flush to sewer or allow material to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Vacuum or sweep material and place in a disposal container. Provide adequate ventilation.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling: Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc., is not recommended. Use only in well-ventilated areas. Handle and open container with care. Do not eat or drink when using. Wash hands before eating, drinking, or smoking. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area. (See section 10)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS			
Exposure Guidelines			
Occupational Exposure Limits			
Ingredient	OSHA-PEL	ACGIH-TLV	
Silica, crystalline, quartz	((10 mg/m3)/(%SiO2+2) TWA (resp)) ((30 mg/m3)/(%SiO2+2) TWA (total)) ((250)/(%SiO2+5)	0.025 mg/m³	
Portland cement	15 mg/m ³ (total); 5 mg/m ³ (resp)	1 mg/m ³ (no asbestos and <1% crystalline silica, respirable fraction)	
Limestone	250 mppcf: 0.1 mg/m ³ TWA	2 mg/m3 TWA	
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m³	
Aluminum Oxide	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	1 mg/m ³ TWA (respirable fraction)	

EXPOSURE CONTROLS

Engineering Controls: Use adequate ventilation to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin Protection:

Hand Protection: Wear suitable gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering face-piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

Appearance	Powder
Color	White to off-white
Odor	Not Available
Odor Threshold	Not Available
Physical State	Solid
pH	Not Available
Melting Point/Freezing Point	Not Available
Initial Boiling Point and Boiling Range	Not Available
Flash Point	Not Available
Evaporation Rate	Not Available
Flammability	Not Flammable
Lower Flammability/Explosive Limit	Not Available
Upper Flammability/Explosive Limit	Not Available
Vapor Pressure	Not Available
Vapor Density	Not Available
Relative Density/Specific Gravity	2.5 to 2.7
Solubility	Partial
Partition coefficient: n-octanol/water	Not Available
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
Viscosity	Not Available
Oxidizing Properties	Not Available
Explosive Properties	Not Available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY No dangerous reaction known under conditions of normal use. CHEMICAL STABILITY Stable under normal storage conditions. Keep dry in storage. POSSIBILITY OF HAZARDOUS REACTIONS No dangerous reaction known under conditions of normal use. CONDITIONS TO AVOID Heat. Incompatible materials. Moisture. INCOMPATIBLE MATERIALS Acids. Ammonium salts. Aluminum. Alkalis. HAZARDOUS DECOMPOSITION PRODUCTS May include, and are not limited to: oxides of carbon.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.

Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Acute Toxicity:

Ingredient	LC50	LD50
Silica, crystalline, quartz	Not available.	Oral 500 mg/kg, rat
Portland Cement	Not available.	Not available.
Limestone	Not available.	Oral 500 mg/kg, rat
Calcium Carbonate	Not available	Oral 6450 mg/kg, rat
Aluminum Oxide	Not available	Oral ≥5000 mg/kg, rat
Calculated	overall Chemical Acute Te	oxicity Values
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	Not available.	Not available.
Inguadiant	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*	
Ingredient		
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65	
Portland Cement	G-A4	
Limestone	KHC, 100C-68-1, A2	
Calcium Carbonate	Not listed	
Aluminum Oxide	Not listed	
	(* See Section 15)	

(* See Section 15)

DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT-TERM AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory Sensitization: Based on available data, the classification criteria are not met.

Skin Sensitization: May cause an allergic skin reaction.

STOT-Single Exposure: May cause respiratory irritation.

Chronic Health Effects:

Carcinogenicity: May cause cancer.

Germ Cell Mutagenicity: This product is not classified as a mutagen.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met. **Teratogenicity:** Not hazardous by WHMIS/OSHA criteria. **Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic Materials: Notavailable.

Other Information: Not available.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

PERSISTENCE AND DEGRADABILITY

Not available.

BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

MOBILITY IN SOIL

Not available.

OTHER ADVERSE EFFECTS

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. **Other Disposal Recommendations:** Not available

SECTION 14: TRANSPORT INFORMATION

UN NUMBER

Not regulated.

UN PROPER SHIPPING NAME

Not applicable.

TRANSPORT HAZARD CLASS (ES)

Not applicable.

ENVIRONMENTAL HAZARDS

Not available.

SPECIAL PRECAUTIONS

Do not handle until all safety precautions have been read and understood.

SECTION 15: REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SARA Title III				
Ingredient	Section 302 (EHS) TPO (lb.)	Section 304 EHS RO (lb.)	CERCLA RO (lb.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland Cement	Not listed.	Not listed.	Not listed.	Not listed.
Magnesium Oxide	Not listed.	Not listed.	Not listed.	Not listed.
Calcium Carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Aluminum Oxide	Not listed.	Not listed.	Not listed.	Listed.

California Proposition 65: This product contains a chemical known to the state of California to cause cancer.

WHMIS Classification(s):

Class D2A – Carcinogenicity Class D2A - Chronic Toxic Effects Class D2B - Skin/Eye Irritant

Class E – Corrosive Material

TSCA:		WHMIS Hazard Symbols:	
Ingredie	ent USA TSCA LISTEI		
Silica, crystalline			
Portland Cement			
Magnesium Oxid	le Yes		() i // E
Calcium Carbona	Calcium Carbonate Yes		
Aluminum Oxide	e No		
NEDA Notio	onal Fire Protection Association	HMIS-Hazardous Mater	ials Identification System
Health:		Health:	2*
Fire:	0	Fire:	0
Reactivity:	0	Reactivity:	0
	0	1 = slight, $2 = $ moderate, $3 = $ severe, $4 = $ extr	
* SOURCE AGEN	NCY CARCINOGEN CLASSIFICA		
SOURCE AGE	CI CARCINOGEN CLASSIFICA	110115.	
CP65	California Proposition 65		
	_		
OSHA (O)	Occupational Safety and Health	n Administration.	
ACGIH (G)	American Conference of Govern	nmental Industrial Hygienists.	
	A1 - Confirmed human carcinogen		
	A2 - Suspected human carcinogen		
	A3 - Animal carcinogen.		
	A4 - Not classifiable as a human ca		
	A5 - Not suspected as a human care	cinogen.	
IARC (I)	International Aganay for Bases	nch on Concor	
	International Agency for Research on Cancer. 1 - The agent (mixture) is carcinogenic to humans.		
	2A - The agent (mixture) is carcinogenic to numans. 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of		
	carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.		
	2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental		
	animals.		
	3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.		
		rcumstance) is probably not carcinogenic to	
NTP (N)	National Toxicology Program.		
1 - Known to be carcinogens.			
	2 - Reasonably anticipated to be car	remogens.	

SECTION 16: OTHER INFORMATION

Date of Preparation:	May 28, 2015
Version:	Initial Issue
Revision Date:	
Prepared by:	Melanie Mitz

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.