

Hard working, deep penetrating cleaner that degreases all filters without harm to the media.

FEATURES & BENEFITS

Contains strong cleaning compounds and releasing agents

Complex formula created with wetting agents and surfactants

Effective for use with all filters

Quickly loosens material buildup in filters

Increases filter efficiency

Extends the life of the filter media

QUICK CLEAN FOR SAND FILTERS:

With pump running and filter in the backwash position, add 6 to 16 ounces of this product into the skimmer. Remove the basket and other materials from the skimmer before adding the product.

OPTIONAL SAND FILTER CLEANING:

Add this product directly into the filter media and let it soak for 4 hours or longer. After 4 to 8 hours, with the filter valve in the backwash position, start the pump. Continue normal filter operation once the discharge is clear.

CARTRIDGE AND D.E. FILTER CLEANING:

Remove filter media from the holding tank and rinse off any excess debris from the filter pleats. Spray this product directly on to the filter pleats, start at the top and work down the filter. Allow cleaner to stand a minimum of 5 minutes before rinsing the filter.

OPTIONAL CARTRIDGE AND D.E. FILTER CLEANING:

In an appropriate sized pail, add 16 ounces of this product to 2 1/2 gallons of fresh water. Allow the filter media to soak for 30 minutes, then remove and rinse. Do not soak filters in steel, aluminum or metal containers.