

In-Wall Timer - Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, DPST, 15 Minute Max, Without Hold, Silver

Item FF415M



PRODUCT DESCRIPTION

The FF Series Commercial Countdown Timers are designed to replace any standard wall switch and do not require electricity to operate. These energy-efficient switches automatically limit the ON times for fans, lighting, motors, heaters, and other energy consuming loads. A commercial "brushed metal" look plate (plastic construction) meets NEC requirements.

FEATURES

- ▶ 15-Minute timer
- ▶ DPST (Double-Pole Single-Throw)
- ▶ Breaks circuit at end of timing cycle
- ▶ No electricity required to operate
- ▶ Replaces any standard or decorator single-gang wall switch
- ▶ Automatically limits ON time for energy consuming loads
- ▶ Quick and easy installation
- ▶ Time-saving up front terminal connection with teeter-type terminals
- ▶ Brushed metal look switch plate meets NEC requirements (plate is included)
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ No neutral connection is required

APPLICATIONS

- ▶ Bathroom Fans
- ▶ Garage Lights
- ▶ Storage Closets
- ▶ Whirlpools
- ▶ Lights
- ▶ Whole House Fans

TECHNICAL DATA

General	
Model Number	FF415M
Description	Spring Wound Countdown Timer, Commercial, 125-277 VAC, 50/60 Hz, DPST, 15 Minute Max, Without Hold, Silver
UPC Code	078275184343
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty	1-Year limited
Application Compatibilities	Incandescent; Fluorescent; CFL; LED
Harmonized Code	9107.00.8000

Control Specifications	
Operation Mode	Countdown
Countdown Time	15 min
Hold Mode Included	No
Mechanism Type	Analog/Mechanical

Mechanical Specifications	
Wall Plate Configurations	Single-Gang; Multi-Gang

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.25 in
-----------------------------------	------------------------

Material Specifications

Color	Silver
Includes Wall Plate	Yes

Load Ratings

Resistive (Heater)	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten (Incandescent) Range(s)	7 A, 125 VAC, 50/60 Hz, 875 W
Motor Range(s)	1 HP, 125 VAC; 2 HP, 250 VAC

Electrical Specifications

Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Wiring Configurations	Single
Switch Type	DPST
Neutral Connection Required	No

Environmental Specifications

Temperature (operation)	40 - 120 °F / 4 - 49 °C
-------------------------	-------------------------

Packaging

Shipping Weight (lbs)	0.349
Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in

Standards and Certifications

CSA Certification	cCSAus
Other Certifications and Compatibilities	RU
California Proposition 65	DEHP
PDF Standards and Certifications	cCSAus; RU

ACCESSORIES



146MT577
Knob-Wall Switch FF Series - White



146MT579
Knob-Wall Switch FF Series - Black



FF15MP
Plate for 15-Min without HOLD, Silver (FF15MC,
FF315M, FF415M)