_ _ _ _ _ _ _ _ _ _ _

Product Name: OPTILON, Viking Blue Product Code: 858

SECTION 1: IDENTIFICATION

 Product Name
 OPTILON, Viking Blue

 Product Code #
 858

 Identified Uses
 Protective Coating

 Manufacturer:
 Kelly Technical Coatings 1445 South 15th Street P.O. Box 3726 Louisville, Kentucky 40201-3726

 Emergency Contact Number:
 Day: 502-636-2561

 Information Teleptone Number:
 502-636-2561

SECTION 2 : HAZARDS IDENTIFICATION

Flammable Liquid 3 Aspiration Hazard 1 Skin Irritant 2 Eye Damage/Irritation 2a Acute Toxicity - Inhalation 4 Carcinogenicity 2 Specific Target Organ Toxicity (Single Exposure) 3

GHS Classification

GHS Label Elements

Hazard Symbols



Signal	Word	Danger
--------	------	--------

Hazard Statements

- H226 Flammable liquid and vapor
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H351 Suspected of causing cancer
- H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No Smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapor/spray.
- P271 Use only outdoors or in well-ventilated area.
- P280 Wear PPE to protect skin/eyes.
- P281 Use personal protective equipment as required.

Response

- P312 Call a poison center or doctor if you feel unwell.
- P363 Wash contaminated clothing and wash before reuse.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

SAFETY DATA SHEET

Product Name: OPTILON, Viking Blue Product Code: 858

	P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P308 + P313 IF exposed or concerned: Get medical advice/attention.
	P332 + P313 If skin irritation occurs: Get medical advice/attention.
	P337 + P313 If eye irritation persists: Get medical advice/attention.
	P303 + P361 + P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
	P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue
	rinsing.
Storage/ Disp	oosal
· ·	P405 Store locked up.
	P501 Dispose of contents/container in accordance with federal, state, provincial, and local regulations.
	P403 + P233 Store in well ventilated place. Keep container tightly closed.
	P403 + P235 Store in a well-ventilated place. Keep cool.

Other Hazards OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

SECTION 3: COMPOSITION INFORMATION

Chemical Designation	CAS No.	% by Weight
nepheline syenite	37244-96-5	30 - 40%
light aromatic naphtha	64742-95-6	10 - 20%
4-chlorobenotrifluoride	98-56-6	5 - 10%
1,2,4 trimethylbenzene	95-63-6	5 - 10%
VOC Exempt solvent	Trade Secret	5 - 10%
titanium dioxide	13463-67-7	1 - 5%
cumene	98-82-8	0.1 - 1%

SECTION 4: FIRST AID MEASURES

Show this safety data sheet to the doctor in attendance
Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get
mmediate medical attention.
Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.
Nove to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.
Do not induce vomiting – seek immediate medical attention.
Freat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Specific Hazards	Closed containers may rupture if exposed to fire or extreme heat.
arising from the	
Chemical	
Special protective	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective
Equipment:	gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Use personal protective equipment. Remove all sources of ignition.
Environmental	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from
Precautions	entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages
	cannot be contained.
Methods for Clean-up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface
	thoroughly.
Other Information	None known

Product Name: OPTILON, Viking Blue Product Code: 858

SECTION 7 : HANDLING & STORAGE

Handling:	Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal
	protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge,
	all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.
Storage:	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*21

HMIS CODE: 4 - SEVERE HAZARD, 3 - SERIOUS HAZARD, 2 - MODERATE HAZARD, 1 - SLIGHT HAZARD, 0 - MINIMAL HAZARD, * - Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

Exposure Limits		
Hazardous Components	OSHA PEL	ACGIH TLV
nepheline syenite	5 ppm (R)	NE
light aromatic naphtha	NE	NE
4-chlorobenotrifluoride	NE	NE
1,2,4 trimethylbenzene	25 ppm	25 ppm
VOC Exempt solvent	1000 ppm	500 ppm
titanium dioxide	15 mg/m3	10 mg/m3
cumene	50 ppm	50 ppm

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit (R) = Respirable fraction

Engineering Measures	Ensure adequate ventilation, especially in confined areas.		
Personal Protective Equipment Eyes/Face: Skin: Respiratory Protection:	Safety goggles or full face shield Protective gloves and impervious clothing. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.		
Hygiene Practices:	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES Appearance: liquid Odor: Solvent odor Odor threshold: Not determined VOC lb/gal 2.26 VOC (g/L) 270.90 VOC (lb/gal) less exempt 2.77 VOC (g/L) less exempt 331.93 Relative Density (LB/GAL): 10.67 Specific Gravity (g/L): 1.28 Flash Point (F): 110 Flammability: Not determined Upper/lower flammability limits: Not available Auto-ignition temperature: Not determined Decomposition temperature: Not determined Evaporation rate : Not available Vapor Pressure (mmHg): Not available Vapor Density : Not available Initial Boiling Point (F): Not available Boiling Point Range (F): Not available Freezing Point (F): Not determined Melting Point (F): Not determined pН Not available Viscosity Not available Solubility (ies): Not determined Partition coefficient: n-Not determined octanol/water

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Conditions to Avoid: Stable under normal conditions. Hazardous polymerization does not occur. Keep away from open flames, hot surfaces, static electricity and sources of ignition.

SAFETY DATA SHEET

Product Name: OPTILON, Viking Blue Product Code: 858

Date issued: 5/27/2015

Materials to Avoid:

Hazardous Decomposition Products: Possibility of Hazardous Reactions: Incompatible with strong acids and bases and strong oxidizing agents. Thermal decomposition can lead to release of irritating gases and vapors. None under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
nepheline syenite	NA	NA	NA
light aromatic naphtha	8,400	NA	NA
4-chlorobenotrifluoride	NA	NA	NA
1,2,4 trimethylbenzene	5,000	18,000	NA
VOC Exempt solvent	NA	NA	NA
titanium dioxide	10,000	10,000	6.82
cumene	NA	NA	NA

Chronic Toxicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Component	IARC	NTP	OSHA
titanium dioxide	2B - Possible Human Carcinogen	Not listed	Listed
cumene	2B - Possible Human Carcinogen	Not listed	Listed

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints.

SECTION 12 : ECOLOGICAL INFORMATION

No ecological information available

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

SECTION 14 : TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA:

Yes - All components are listed or exempt

Cas No.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard	YES
Chronic Health Hazard	YES
Fire Hazard	NO
Sudden Release of Pressure Hazard	NO
Reactive Hazard	NO

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical Designation

Weight %

SAFETY DATA SHEET

_ _ _ _ _

Product Name: OPTILON, Viking Blue Product Code: 858

Date issued: 5/27/2015

_ _ _ _ _ _

—	_	—	_	—	_	_	_	—	_	—	—	_	_	—	_	_	_	-
		1,2,4 1	trimet	hylbei	nzene				95	-63-6						5 - 10	%	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)							
Chemical Designation	Cas No.	Weight %					
cumene	98-82-8	0.1 - 1%					

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 5/27/2015 VER 04

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.