Product Name: PARALON 2, BLACK VOC COMPLIANT

Product Code: 297 Date issued: 5/27/2015

SECTION 1: IDENTIFICATION

Product Name PARALON 2, BLACK VOC COMPLIANT

Product Code # 297

Identified Uses Protective Coating

Manufacturer: Kelley Technical Coatings

1445 South 15th Street P.O. Box 3726

Louisville, Kentucky 40201-3726

Emergency Contact Number: Day: 502-636-2561 Night: 800-424-9300

Information Telephone Number: 502-636-2561

SECTION 2: HAZARDS IDENTIFICATION

Flammable Liquid 3 Aspiration Hazard 1 Skin Irritant 2

Eye Damage/Irritation 2a Acute Toxicity - Inhalation 4

Carcinogenicity 2

Specific Target Organ Toxicity (Single Exposure) 3

GHS Classification

GHS Label Elements

Hazard Symbols



Signal Word Danger

Hazard Statements

H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation H319 Causes serious eye irritation H332 Harmful if inhaled

H351 Suspected of causing cancer

H336 May cause drowsiness or dizziness

Precautionary statements

Prevention

Response

Storage/ Disposal

Other Hazards OSHA Regulatory Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200)

SECTION 3: COMPOSITION INFORMATION

Chemical Designation CAS No. % by Weight

Product Name: PARALON 2, BLACK VOC COMPLIANT

Product Code: 297 Date issued: 5/27/2015

VOC Exempt solvent	Trade Secret	10 - 20%
nepheline syenite	37244-96-5	10 - 20%
4-chlorobenotrifluoride	98-56-6	10 - 20%
2-butoxyethanol	111-76-2	5 - 10%
light aromatic naphtha	64742-95-6	5 - 10%
1,2,4 trimethylbenzene	95-63-6	1 - 5%
naphtha, heavy aromatic	64742-94-5	1 - 5%
carbon black	1333-86-4	1 - 5%
naphthalene	91-20-3	0.1 - 1%

SECTION 4: FIRST AID MEASURES

General Advice Show this safety data sheet to the doctor in attendance

Eyes: Flush with plenty of cool water for at least15 minutes, holding eyelids apart for thorough irrigation. If irritation persists, get

immediate medical attention.

Skin: Wash affected area thoroughly with soap and water. If skin irritation persists, get immediate medical attention.

Inhalation: Move to fresh air. Restore breathing. If breathing is difficult, get immediate medical attention.

Ingestion: Do not induce vomiting – seek immediate medical attention.

Notes to Physician Treat symptomatically

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards Closed containers may rupture if exposed to fire or extreme heat.

arising from the Chemical

Special protective As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective

Equipment: gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment. Remove all sources of ignition.

Environmental Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

Methods for Clean-up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface

thoroughly.

Other Information None known

SECTION 7: HANDLING & STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear appropriate personal

protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge,

all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep in properly labeled containers.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HMIS is a Health, Flammability and Reactivity rating: 2*21

HMIS CODE: 4 – SEVERE HAZARD, 3 – SERIOUS HAZARD, 2 – MODERATE HAZARD, 1 – SLIGHT HAZARD, 0 – MINIMAL HAZARD, * – Chronic Hazard Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual conditions of use.

Exposure Limits

Hazardous Components OSHA PEL ACGIH TLV

Product Name: PARALON 2, BLACK VOC COMPLIANT

Product Code: 297 **Date issued:** 5/27/2015

VOC Exempt solvent	1000 ppm	500 ppm
nepheline syenite	5 ppm (R)	NE
4-chlorobenotrifluoride	NE	NE
2-butoxyethanol	50 ppm	20 ppm
light aromatic naphtha	NE	NE
1,2,4 trimethylbenzene	25 ppm	25 ppm
naphtha, heavy aromatic	NE	NE
carbon black	3.5 mg/m3	3 mg/m3 (I)
naphthalene	10 ppm	5 ppm

NE = None established NA = Not available (C) = Ceiling limit (I) = Inhalable fraction (IFV) = Inhalable fraction and vapor STEL = Short term exposure limit

(R) = Respirable fraction

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective

Equipment

Appearance:

Safety goggles or full face shield Eyes/Face: Skin: Protective gloves and impervious clothing.

liquid

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically **Respiratory Protection:**

qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH

approved respirator specified for paint spray or organic vapors.

Hygiene Practices: Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after

handling. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Odor:	Solvent odor	Odor threshold:	Not determined
VOC lb/gal	1.78	VOC (g/L)	213.16
VOC (lb/gal) less exempt	2.75	VOC (g/L) less exempt	329.60
Relative Density (LB/GAL):	9.47	Specific Gravity (g/L):	1.14
Flash Point (F):	110		
Flammability:	Not determined	Upper/lower flammability limits:	Not available
Auto-ignition temperature:	Not determined	Decomposition temperature:	Not determined
Evaporation rate:	Not available		
Vapor Pressure (mmHg):	Not available	Vapor Density:	Not available
Initial Boiling Point (F):	Not available	Boiling Point Range (F):	Not available
Freezing Point (F):	Not determined	Melting Point (F):	Not determined
pН	Not available	Viscosity	Not available

Solubility (ies): Not determined Not determined

Partition coefficient: n-

octanol/water

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions. Hazardous polymerization does not occur. Conditions to Avoid: Keep away from open flames, hot surfaces, static electricity and sources of ignition.

Materials to Avoid: Incompatible with strong acids and bases and strong oxidizing agents. Hazardous Decomposition Products: Thermal decomposition can lead to release of irritating gases and vapors.

Possibility of Hazardous Reactions: None under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute	Toxicity

Component	LD50 Oral mg/kg (Rat)	LD50 Dermal mg/kg (Rabbit)	LC50 Inhalation mg/L (Rat, 4 hr.)
VOC Exempt solvent	NA	NA	NA
nepheline syenite	NA	NA	NA
4-chlorobenotrifluoride	NA	NA	NA
2-butoxyethanol	470	220	2.2
light aromatic naphtha	8,400	NA	NA
1,2,4 trimethylbenzene	5,000	18,000	NA

Product Name: PARALON 2, BLACK VOC COMPLIANT

Product Code: 297 Date issued: 5/27/2015

naphtha, heavy aromatic	NA	NA	NA
carbon black	15,400	3,000	NA
naphthalene	NA	NA	NA

Chronic Toxicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

ComponentIARCNTPOSHAcarbon black2B – Possible Human CarcinogenNot listedListednaphthalene2B – Possible Human CarcinogenProbable Human CarcinogenListed

Per IARC Summary of Data Reported, Subsection 5.1: No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint.

SECTION 12: ECOLOGICAL INFORMATION

No ecological information available

SECTION 13: DISPOSAL CONSIDERATION

Waste Disposal Method Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your

sanitation department or state-designated environmental protection agency for more disposal options.

SECTION 14: TRANSPORT INFORMATION

Contact the manufacturer for shipping information.

SECTION 15: REGULATORY INFORMATION

US TSCA: Yes – All components are listed or exempt

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard YES
Chronic Health Hazard YES
Fire Hazard NO
Sudden Release of Pressure Hazard NO
Reactive Hazard NO

SARA 313

Section 313 OF Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical DesignationCas No.Weight %1,2,4 trimethylbenzene95-63-6< 5%</td>

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

Chemical DesignationCas No.Weight %naphthalene91-20-30.1 - 1%

Any Target HAP listed in this section is not an OSHA Carcinogen unless listed as such in Section 11 under Chronic Toxicity.

State Regulations

Product Name: PARALON 2, BLACK VOC COMPLIANT

Product Code: 297

Date issued: 5/27/2015

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

SECTION 16: OTHER INFORMATION

Date issued: 5/27/2015 VER (

The above Information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith. No warranty is implied with respect to the quality or the specification of the product and the user must satisfy himself that the product is entirely suitable for his purposes.