



**ABOVEGROUND
SYSTEMS**

CLEAN & CLEAR[®]

Aboveground Cartridge
Filter System

So clean. So clear. So easy.

We've paired our dependable OptiFlo[®] Aboveground Pump with our highly efficient Clean & Clear Filter to create this high-performance system for aboveground pools. Rugged, efficient and simple to operate, these perfectly matched components will keep your aboveground pool clean, clear and inviting—with minimal care.

So, if you're looking for top-end aboveground system performance that's easy to maintain, look no further than the Clean & Clear Filter System from Pentair.

pentair.com/cleanclear



▲
**CLEAN & CLEAR ABOVEGROUND
CARTRIDGE FILTER SYSTEM**



CLEAN & CLEAR® ABOVEGROUND CARTRIDGE FILTER SYSTEM

Carefree and convenient.

Like all Pentair cartridge filter systems, the Clean & Clear Filter System features an easy-to-clean filter cartridge. All models are equipped with easy spin-on unions for fast and economical plumbing hookups.

KEY FEATURES

- **Single-piece filter base and body**
Designed for strength, durability and quiet operation.
- **Fiberglass-reinforced construction**
For strength, durability and reliability.

FILTER KEY FEATURES

- **Removable filter cartridge**
For quick, convenient cleaning.
- **Filter lock ring and 1" filter drain**
Allows for quick and easy servicing.

- **Optimum filtration efficiency**
Hi-Flow™ Manual Air Relief Valve and continuous internal air relief work to help eliminate air accumulation and maintain optimum filtration efficiency.

PUMP KEY FEATURES

- **Proprietary Totally Enclosed Fan-Cooled (TEFC) Motor**
Enhanced design and balanced flow enable energy efficiency and reduce operating costs.
- **Large strainer basket with see-thru lid**
For easy inspection and cleaning.



CLEAN & CLEAR ABOVEGROUND CARTRIDGE FILTER SYSTEM

| Model Number | Filter Area Sq. Ft. | Turnover Capacity-Res. (Gallons) | | |
|--------------|---------------------|----------------------------------|---------|---------|
| | | 8 hrs. | 10 hrs. | 12 hrs. |
| PNCC00500E | 50 | 24,000 | 30,000 | 36,000 |
| PNCC00750E | 75 | 36,000 | 45,000 | 54,000 |
| PNCC01000E | 100 | 48,000 | 60,000 | 72,000 |
| PNCC01250E | 125 | 60,000 | 75,000 | 90,000 |
| PNCC01500E | 150 | 72,000 | 90,000 | 108,000 |
| PNCC01750E | 175 | 72,000 | 90,000 | 108,000 |
| PNCC02000E | 200 | 72,000 | 90,000 | 108,000 |

Flow rate and turnover capacity based on filter.