

	RUBBER-BASED			
	TYPE A	A-2	PRO 2000	ULTRA PRO 2000
SURFACE TYPES	<ul style="list-style-type: none"> Existing chlorinated rubber Bare concrete Marcite Plaster 	<ul style="list-style-type: none"> Existing chlorinated rubber Existing synthetic rubber Bare concrete Marcite Plaster 	<ul style="list-style-type: none"> Existing chlorinated rubber Bare concrete Marcite Plaster 	<ul style="list-style-type: none"> Existing chlorinated rubber Bare concrete Marcite Plaster
PREP AGENT	Ramuc Clean & Prep Solution	Ramuc Clean & Prep Solution	Ramuc Clean & Prep Solution	Ramuc Clean & Prep Solution
DO NOT APPLY TO (NON-COMPATIBLE SURFACES OR COATINGS)	<ul style="list-style-type: none"> Fiberglass Gelcoat Spas/Hot tubs Metal Existing acrylic Salt water pool systems Existing epoxy 	<ul style="list-style-type: none"> Fiberglass Gelcoat Spas/Hot tubs Metal Existing acrylic Salt water pool systems Existing epoxy 	<ul style="list-style-type: none"> Fiberglass Gelcoat Spas/Hot tubs Metal Existing acrylic Salt water pool systems Existing epoxy 	<ul style="list-style-type: none"> Fiberglass Gelcoat Spas/Hot tubs Metal Existing acrylic Salt water pool systems Existing epoxy
FINISH	High-gloss	High-gloss	Flat	Flat
PACKAGE SIZE	1 & 5 gallon	1 & 5 gallon	1 & 5 gallon	1 & 5 gallon
COVERAGE	<ul style="list-style-type: none"> 200-300 sq. ft./gallon on bare surfaces 350-400 sq. ft./gallon on recoats 	<ul style="list-style-type: none"> 200-300 sq. ft./gallon on bare surfaces 300-400 sq. ft./gallon on recoats 	<ul style="list-style-type: none"> 150-175 sq. ft./gallon on bare surfaces 250-300 sq. ft./gallon on recoats 	<ul style="list-style-type: none"> 175-200 sq. ft./gallon on bare surfaces Up to 300 sq. ft./gallon on recoats
SERVICE LIFE	5 years	4 years	1-2 years	1-2 years
APPLICATION	<ul style="list-style-type: none"> Brush Roller (max 3/8" thickness) Airless or conventional sprayer 	<ul style="list-style-type: none"> Brush Roller (max 3/8" thickness) Airless or conventional sprayer 	<ul style="list-style-type: none"> Brush Roller (max 3/8" thickness) Airless or conventional sprayer 	<ul style="list-style-type: none"> Brush Roller (max 3/8" thickness) Airless or conventional sprayer
DRY TIME BETWEEN COATS	24 hours	24 hours	24 hours	24 hours
DRY/CURE TIME BEFORE FILLING	<ul style="list-style-type: none"> Outdoor: 5-7 days Indoor: 10-14 days 	<ul style="list-style-type: none"> Outdoor: 5-7 days Indoor: 10-14 days 	<ul style="list-style-type: none"> Outdoor: 5-7 days Indoor: 10-14 days 	<ul style="list-style-type: none"> Outdoor: 5-7 days Indoor: 10-14 days
CLEAN-UP	Ramuc Thinner	Ramuc Thinner	Ramuc Thinner	Ramuc Thinner
VOC COMPLIANT	No*	Yes	No*	Yes, except California