

# Residential Ladder



- Tubing: 1.90" OD
- Wall Thickness: .049"
- Stainless Steel: 304 or 316L Marine Grade\* (add -MG to part number)
- Treads: LTDF-101 Plastic (Econoline) or LTDF-103 Stainless Steel (Elite)
- Bends: 6" Radius
- Options: Powder-coating and SealedSteel Salt Friendly available
- Recommended anchors: AS-100B (order separately)
- Recommended escutcheon: EP-100F (order separately)

\* Minimum requirement for salt pools is 316L Marine Grade

Econoline	Shipping Weight	Elite	Shipping Weight	Description	Shipping		
					Length	Width	Height
RLF-24E-2A	21 lbs	RLF-24S-2A	22 lbs	2-step ladder	60"	28"	2"
RLF-24E-3B	24 lbs	RLF-24S-3B	25 lbs	3-step ladder	65"	28"	2"
RLF-24E-4C	29 lbs	RLF-24S-4C	30 lbs	4-step ladder	82"	28"	2"
RLF-24E-5D	32 lbs	RLF-24S-5D	33 lbs	5-step ladder	90"	28"	2"

#### Note:

- Frames extend 6½" from the pool wall. Frame is secured to the pool deck with two anchor sockets on 20" centers (Elite model) or 19" centers (Econoline model). The lower end of the frame is bent to meet the pool wall and fitted with two white rubber bumpers (VRB-100A).

